

E3500 TRACE DETECTOR

Detects Explosives



CHEMILUMINESCENCE

TRACE DETECTION



The rugged E3500 uses chemiluminescence to detect homemade, military and commercial explosive compounds, including ICAO taggants, plastics, ammonium nitrate, black powder, other nitrates and peroxide-based explosives such as TATP and HMTD.

- Delivers laboratory-grade accuracy to the field
- Rapid, accurate and easy to read results in seconds
- Detects nitrogen- and peroxide-based explosives
- Battery powered for portability

APPLICATIONS:

- Force Protection
- Customs and Borders
- VIP Screening
- Embassies and Consulates
- Royal and Diplomatic Protection
- Critical Infrastructure
- High Security Events



Comes field-ready in a protective case / backpack with two batteries, charger, trace samples, sampling screens and other accessories.

Build to withstand rough handling and harsh environments, the E3500 packs potent detection capability into a light-weight, durable thermoplastic housing. The handheld E3500 analyzes both particulates and vapors in seconds, without the need for radioactive isotopes or carrier gases.

A global leader in explosives, chemical and narcotics detection, Scintrex Trace is Autoclear's Canadian-based trace detection division. Like Autoclear's flagship X-ray systems, these products deliver unsurpassed accuracy, speed and reliability for detecting the most dangerous and cleverly concealed threats.

SPECIFICATIONS

Detector:	Chemiluminescence
Analysis Time:	8 seconds
Explosives Detected:	PETN, RDX, TNT, dynamite, Semtex, C-4, black powder, ammonium and urea nitrates, NG, ICAO taggants, EGDN and DMNB, TATP, peroxides, chlorates
Sensitivity:	Nanogram
Sample Collection:	Particulates and vapors
Warm-up Time:	None, after one minute start
Alarms:	LED indicator lights and audible alarm
Power Supply:	12 V DC rechargeable four hour battery pack
Input Voltage:	90-264 VAC, 50-60 Hz universal switching
Unit Weight:	3.0 kg (6.6 lbs.) with battery
Unit Dimensions: (L x W x H)	50.0 x 14.0 x 11.0 cm 20.0 x 5.5 x 4.3 in.
Shipping Weight:	8.63 kg (19 lbs.)
Shipping Dimensions: (L x W x H)	72.0 x 41.5 x 32.0 cm 28.4 x 16.3 x 12.6 in.
Operating Temp:	0° to 55°C (32° to 131°F)
Storage Temp:	-5° to 65°C (23° to 149°F)
Communication:	RS-232 serial output port
Data Storage:	1,000 retrievable data records
Options:	12 V AC battery, external battery, printer



World Headquarters

2 Gardner Road
Fairfield NJ 07004 USA

Tel. 1 973.276.6000
Toll-free 1 800.231.6414
Fax. 1 973.276.6162

info@autoclear.com

Autoclear/Scintrex

300 Parkdale Ave., Ottawa
Ontario, Canada K1Y 1G2

Tel. 1 613.224.1061
Fax. 1 613.224.2603

info@scintrextrace.com

ISO 9001-2008 REGISTERED

2011-2014 © Autoclear, CheckGate®, Control Screening®, Dynavision®, HandWand® and Scintrex® are among our many registered trademarks. All rights reserved. Autoclear reserves the right to update this information presented in this document at anytime, without notice.